

B-FV4D B-FV4T

Desktop Printers

Datasheet

- > The easy to use and cost-effective desktop labelling solution.
- > Your flexible office assistant – for all printing applications.
- > The B-FV4 desktop printer series can seamlessly integrate into existing systems, regardless of the specification or printing requirement.
- > Designed to be compact, stylish, and unobtrusive, yet powerful and flexible for any environment and application – one size really does fit all!



The Perfect Fit

We have designed the B-FV4 printer series to be the perfect silent office helper – small enough to fit into the tightest of spaces, with the flexibility to integrate into any environment. Stylish and sleek, yet rugged and powerful with print speeds of up to 6 ips, it handles even demanding printing applications with ease.

Regardless of the current application, the B-FV4 series ‘speaks your language’, allowing straightforward integration into existing systems. With a whole host of connectivity options as standard, this impressively flexible printer really is equipped to manage the most diverse printing requirements.

One size fits all - whether direct thermal printing or using thermal ribbons, simply choose the options to suit your application.

Designed for the User

For ease of use and maintenance, the B-FV4 series has been designed with the user in mind. Drop-in paper loading allows quick and easy changes to media, and critical parts can be upgraded with a snap-in printhead and platen assembly.

Combined with the all-important Toshiba reliability, the B-FV4 is a rugged and robust workhorse for any environment.

Specifications

General

Print Method	B-FV4D GS & Courier/TS: B-FV4T GS/TS:	Direct thermal Direct thermal/ Thermal transfer
Printhead	Flat head	
Dimensions (W x D x H)	GS: Courier & Linerless models: TS:	184 x 226 x 166 mm 184 x 226 x 199 mm 220 x 279 x 182 mm
Weight	B-FV4D GS & Courier/TS: B-FV4T GS/TS:	1.8 kg 2.4 kg
User Interface	2 x LED (colours: green, amber, red), 1 x key	
Operating Temperature/ Humidity	5°C to 40°C / 25-85% non-condensing relative humidity (RH)	
Power Supply	B-FV4D GS & Courier/TS: B-FV4T GS/TS:	AC adaptor (60W) AC adaptor (90W)

Print

Resolution	B-FV4D GS & Courier/TS: B-FV4T GS/TS:	203/300 dpi 203/300 dpi
Max. Print Speed	B-FV4D GS & Courier: B-FV4D TS/GS: B-FV4T GS: B-FV4T TS:	152.4 mm/second 101.6 mm/second 152.4 mm/second 101.6 mm/second
Max. Print Width	B-FV4D GS & Courier/TS: B-FV4T GS/TS:	108/105.7 mm 108/105.7 mm
Max. Print Length	B-FV4D GS & Courier/TS: B-FV4T GS/TS:	995/453.2 mm 995/453.2 mm

Ribbon³⁾

Ribbon Width	B-FV4T GS/TS:	40-110 mm
Ribbon Core	12.7 mm (1/2 inch) or 25.4 mm (1 inch)	
Max. Ribbon Length	B-FV4T GS/TS:	300 m
Max. Outer Core Diameter	B-FV4T GS/TS:	40 mm (12.7 mm core) 65 mm (25.4 mm core)

Media

Alignment	Centred	
Backing Paper Width	25.4-118 mm	
Label Thickness	0.06-0.19 mm	
Inner Media Roll Diameter	25.4 or 38.1mm (optional: 76.2 mm)	
Outer Media Roll Diameter	Standard: Max. 127.0 mm Optional: Max. 203.2 mm	
Media Type	Roll, Fanfold	

ARC Technologie, a.s.
 U Trojice 1042/2, 150 00 Praha 5
 Tel.: 257 326 966, info@arctech.cz
 www.arctech.cz

Software and Connectivity

Emulations	ZPL II, EPL 2, DPL, IPL
Printer Driver	Windows 8/7/Vista (32 bit/64 bit), Windows XP, Windows Server 2008 R2/Server 2008 (64 bit)/Windows Server 2003
Host Interface	Type 1: USB 2.0, LAN 10/100 Base (excl. China) Type 2: USB 2.0, LAN 10/100 Base, RS-232C (max. 115,200 bps) Type 3: USB 2.0, IEEE1284 Courier models: USB 2.0, LAN 10/100 Base, RS-232C (max. 115,200 bps)
Label Software	BarTender Ultra Light

Options

Peel-off module (standard on Courier model), Full cutter module¹⁾,
 Partial cutter module²⁾, External 203 mm OD media stand¹⁾,
 WLAN I/F (802.11b/g)²⁾ or Bluetooth I/F²⁾

¹⁾ not available for Linerless model

²⁾ not available for Courier & Linerless models

³⁾ not available for B-FV4D models (Direct thermal)



Toshiba Tec Germany Imaging Systems GmbH

Carl-Schurz-Str. 7
 41460 Neuss
 Germany

Telephone / Fax

+49 2131-1245-0 / +49 2131-1245-402

Website

www.toshibatec.eu

Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data.

It is based on our belief that the most successful organisations are those that communicate information in the most efficient way.

We make that possible through an integrated portfolio of industry specific solutions, all of which reflect Toshiba's commitment to the future of the planet.

For more information please visit:
 www.togetherinformation.com

