

XT-5315

Specification	XT-5315
Processor	Intel G1820 / 2.7GHz / 2M Cache; Intel G3320TE / 2.93GHz / 3M Cache; Intel Core i3-4330TE / 2.4GHz / 4M Cache
System Memory	DDR3 1333 SODIMM x 2, max. 16GB, factory default 4GB (DDR3 1333 / 1600 for Core i3 CPU)
Storage Device	SATA storage x 2; factory default 320GB HDD x 1
Power Supply	12V DC power adaptor, 120W (Optional 150W when equipping with 2nd LCD display LM/TM-3014SLM/TM-3015)
OS Support	Windows 7 / POSReady 7 / Windows Embedded 6.1 Industry / Linux per request
Display	
LCD Display	15" TFT LCD, 1024 x 768 resolution
Touch Function	Trustellit Projected Capacitive Touch supporting 10 pts multi-touch
Brightness adjustment	By digital push button
Connectivity	
LAN Port	10 / 100 / 1000Mb x 2
Serial Port	6, DB9 x 2 + RS485 x 2 on I/O plate, pin header x 2 from service window, 5V support on all COM ports, 12V support on COM 1 to COM 4
UPS Port	Yes
Standard USB Port	6
Powered USB Por	Optional 24V x 1 and 12V x 3 via GENIE Base
Audio	Internal 2W speakers x 1 + Line-out
VGA Port	VGA x 1, 12V support for Posiflex monitors; mini-DP x 1 on service window
CR Port	1, control 2 CR
Physical Dimension	
Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N.W. in Kg)	5.66
Environment	
Operation Condition	0°C ~ 40°C, 20%RH ~ 90%RH (Equipped with HDD); 0°C ~ 50°C, 20%RH ~ 95%RH (Equipped with SSD)
Storage Condition	-20°C ~ 70°C, 10%RH ~ 90%RH
Options	
SSD	Starting from 16GB
SA-105	Side Attachment for XT Series with 3 track MSR
SA-205	Side Attachment for XT Series with 4 track MSR
SA-305	Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor
SA-405	Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor
LM-3010	9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
LM-3014	14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface)
LM-3015	15" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
LM-6007	7" 800 x 480 rear-mount 2nd display for XT series (USB interface)
PD-6080UE	2 x 20 VFD, rear-mount, USB with Virtual COM support
PD-6500UE	2 x 20 LCD, rear-mount, USB with Virtual COM support
PD-6607	7" color LCD graphical line display, rear-mount (USB interfaces)
WiFi	Internal mini-PCIe WiFi module with PIFA Antenna

* For complete listing of the optional attachments, please refer to the website.



Design and Manufacturing in Taiwan by Posiflex Technology Inc.

The product information and specifications are subject to change without prior notice.

2014Q3

Flexible! Powerful! Elegant!

XT-5315

High End Fan-free POS Terminal





In today's retail and hospitality market, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should add something to the overall mood of the store, to lift the shopping experience of the customers.

With the true-flat PCAP touch screen supporting 10 points multi-touch, beautifully sculptured slim body, sexily curved base stand, Posiflex XT-5315 looks right at any elegantly decorated store. And more than just good looks, Posiflex XT-5315 is powerful enough to handle any task imaginable that comes its way.



Looks

Slimmer and sexier than ever, XT Series is a sharp departure from the traditionally more conservative Posiflex terminal design. Every curves and details are carefully thought out to make XT Series one of the most visually desirable terminals in the market.

Flexibility

XT-5315 comes with the selection of two foldable bases, the curvy slim GEN7E Base and the larger but practical GEN8E Base.

The new foldable bases allow XT-5315 to be configured into different configurations. "Flat, Folded Mode" to save the shipping package volume. "Low Profile Mode" to allow greater interaction between cashier and the customers; and the traditional "Full Extended Mode". All this can be achieved with a simple pull of the hidden lever. This one terminal/ multi-configurations concept provides unmatched flexibility to store owners and system integrators alike.



Full Extended Mode



Low Profile Mode



Flat, Folded Mode

Performance

XT-5315 offer a wide range of performance options from Intel Celeron to Intel Core i7 that is powerful enough to process anything throw at it without even breaking a sweat.



Fan-free Design

Fan-free architecture of XT-5315 allow it to run on harsh environments, such as greasy kitchen, without ever worrying about the fan maintenance. It also allows the machine to run quietly, which is ideally suited for the high-end boutique stores or hospital environment.



GEN8E Base

Optional GEN8E Base that integrates internal power adaptor and Powered USB port into the base stand, which allows for clutter free counter.

